

CLASSE

CAP-2100 INTEGRATED AMPLIFIER



The CAP-2100 combines the separate component preamp CP-500 and CA-2100 amplifier into a single elegant and powerful package. Features include balanced and single-ended inputs, dual speaker binding posts, TFT touchscreen display, IR remote and bi-directional RS-232 control.

Specifications

Model CAP-2100

Frequency response 10Hz - 22kHz \pm 0.1dB

Distortion (THD + noise) 0.005% ((unweighted, 0.8vrms/1kHz input, 10Hz - 80kHz)

Preamp section

Sensitivity 1.0Vrms
(balanced input, volume 86)

S/N ratio 95dB typical

Channel separation >95dB @ 20kHz

Power amp section

Power/channel (continuous)
(120VAC line, 1kHz signal regulated to 1% THD + noise into resistive load, all channels driven)

Load (resistive)
8 Ω 100W
4 Ω 200W

Inputs

Single-ended inputs 3pr RCA (incl. 1pr w/phono option) / 100k Ω

Single-ended tape inputs 1pr RCA / 100k Ω

Balanced inputs 1pr XLR / 200k Ω

Outputs

Speaker 2pr

Single-ended (preamp out) 1pr RCA

Balanced none

Tape out 1pr RCA

Power consumption

Idle power consumption 125W

Rated power consumption 260W

Weights & measurements

Width 17.5" (445 mm)

Depth 16.5" (419 mm) (excluding connectors)

Height 4.75" (121 mm)

Gross weight 59 lbs (27 kg)

Net weight 50 lbs (23 kg)